



Windows sizes, outer dimensions in cm

GPL_60	B x L
CK04	55 x 98
CK06	55 x 118
FK06	66 x 118
FK08	66 x 140
MK04	78 x 98
MK06	78 x 118
MK08	78 x 140
MK10	78 x 160
PK06	94 x 118
PK08	94 x 140
PK10	94 x 160
SK06	114 x 118
SK08	114 x 140
SK10	114 x 160
UK04	134 x 98
UK08	134 x 140

1. Mounting batten for window and flashing support.
2. Auxiliary batten for support of the flashing top part.
3. Additional frame made of two layers of battens.
4. If a trimmer is necessary, maintain a safety distance of 10 cm as per drawing.
5. Framing with 1 layer bituminous sheeting (for example V60 S4) with a sufficient width, stapled.
6. After mounting the bituminous sheeting attach in the BDx2000 set enclosed underfelt collar.
7. The underfelt collar and the water drainage gutter are to be pressed under the notched roof felt underlay.
8. The vapor barrier collar is to be fixed in the window rebate according VELUX installation instructions.
9. The roof vapor barrier and the VELUX vapor barrier BBX are to be connected properly along the whole perimeter, for example with taped joints (VELUX BBX tape) and a fixing batten.
10. The covering strip, part of the VELUX inner lining must be sidelong sealed with an elastic joint seal.
11. Inner lining made from 2 x 12.5mm gypsum boards.
12. Cavity is to be filled with insulation material.
13. Possible roof pitch for the presented installation type: from **20° to 55°**.

For more information regarding the improved sound insulation, please contact your local VELUX sales company.

These are non-binding installation proposals, VELUX does not provide design and planning services and assumes no warranty in this relation.

WINDOW TYPE	VELUX GPL, 62 pane, improved sound insulation			
INSTALLATION PRODUCTS	BDX Insulation frame with underfelt collar, water drainage gutter and BBX vapour barrier collar			
FLASHING	EDZ flashing for flat and profiled roof coverings with a height between 1.5 and 4.5cm			
INTERIOR LINING	VELUX inner lining LSB for roof thickness 30cm and LFI window sill			
ROOF CONSTRUCTION	45° Rafter roof or purlin roof, fully insulated roof, with roof underlay, vapour barrier inside, inner sheathing and interior lining			
ROOF COVERING	Tiles			
FORMAT DIN A3	M 1:10/1:5	19.08.2018	Sheet 1 of 1	Detail Nr. 220ENG