



Windows sizes, outer dimensions in cm

| GGU_66 | B x L |
|--------|-----------|
| CK02 | 55 x 78 |
| CK04 | 55 x 98 |
| CK06 | 55 x 118 |
| FK04 | 66 x 98 |
| FK06 | 66 x 118 |
| FK08 | 66 x 140 |
| MK04 | 78 x 98 |
| MK06 | 78 x 118 |
| MK08 | 78 x 140 |
| MK10 | 78 x 160 |
| PK06 | 94 x 118 |
| PK08 | 94 x 140 |
| PK10 | 94 x 160 |
| SK06 | 114 x 118 |
| SK08 | 114 x 140 |
| UK04 | 134 x 98 |
| UK08 | 134 x 140 |

1. After mounting the insulation frame and the window, attach the enclosed underfelt collar.
2. If replacement is necessary, maintain a safety distance of 10 cm as per drawing.
3. The vapor barrier collar is to be fixed in the window rebate according VELUX installation instructions.

4. The roof vapor barrier and the VELUX vapor barrier BBX are to be connected properly along the whole perimeter, for example with taped joints (VELUX BBX tape) and a fixing batten.
5. Inner lining is to be done according interior design detail (non VELUX product)
6. Possible roof pitch for the presented installation type: from 15° to 55°.

For further information regarding VELUX ridge capping, please contact your local VELUX company.

These are non-binding installation proposals, VELUX does not provide design and planning services and assumes no warranty in this relation.

| | | | | |
|-----------------------|---|------------|--------------|-------------------|
| WINDOW TYPE | VELUX GGU glazing 66, VELUX ridge solution | | | |
| INSTALLATION PRODUCTS | BDX insulation frame with waterproofing collar and BBX vapour barrier | | | |
| FLASHING | EKN flashing for recessed installation into slates roof covering up to 1.6cm, ridge covering EKN | | | |
| INTERIOR LINING | VELUX interior lining LSB for roof thickness 30cm, in the ridge area - detail according interior design (non VELUX product) | | | |
| ROOF CONSTRUCTION | 45° Rafter roof or purlin roof, insulation over rafters with roof underlay, vapour barrier inside, no ridge purlin in the area of installation, inner sheathing and interior lining | | | |
| ROOF COVERING | Slates | | | |
| FORMAT DIN A3 | M 1: 10/1:5 | 12.08.2018 | Sheet 1 of 1 | Detail Nr. 271ENG |